


## Rundstangen

### Kupfer




gezogen · gepresst · gegossen

Durchmesser in mm	Kg/m ca.	CW004A Cu-ETP	CW020A / CW021A Cu-HCP / Cu-PHC
1,5	0,02	•	
2,0	0,03	•	
2,5	0,04	•	
3,0	0,06	•	•
4,0	0,11	•	•
4,5	0,14	•	
5,0	0,17	•	•
5,5	0,21	•	
6,0	0,25	•	
6,5	0,30	•	
7,0	0,34	•	
8,0	0,45	•	
8,5	0,50	•	
9,0	0,57	•	
9,5	0,63	•	
10,0	0,70	•	
11,0	0,85	•	
12,0	1,01	•	
13,0	1,18	•	
14,0	1,37	•	
15,0	1,57	•	
16,0	1,79	•	
17,0	2,02	•	
18,0	2,26	•	
19,0	2,52	•	
20,0	2,79	•	•
22,0	3,38	•	
23,0	3,70		•
24,0	4,0	•	
25,0	4,4	•	

## Rundstangen

### Kupfer




gezogen · gepresst · gegossen

Durchmesser in mm	Kg/m ca.	CW004A Cu-ETP	CW020A / CW021A Cu-HCP / Cu-PHC
26,0	4,72	•	
28,0	5,48	•	
29,0	5,88	•	
30,0	6,29	•	•
32,0	7,15	•	
33,0	7,61	•	
35,0	8,56	•	
36,0	9,05	•	
37,0	9,56	•	
38,0	10,09	•	•
40,0	11,18	•	•
42,0	12,32	•	
45,0	14,15	•	•
46,0	14,78	•	
48,0	16,10	•	
50,0	17,47	•	•
51,0	18,17	•	•
55,0	21,13	•	•
60,0	25,15	•	•
65,0	29,52	•	•
70,0	34,23	•	•
75,0	39,30	•	
80,0	44,71	•	•
85,0	50,48	•	
90,0	56,59	•	•
100,0	69,87	•	•
110,0	84,54	•	•
115,0	92,40	•	•
120,0	100,6	•	•
125,0	109,2		•

## Rundstangen

### Kupfer



gezogen · gepresst · gegossen

Durchmesser in mm	Kg/m ca.	CW004A Cu-ETP	CW020A / CW021A Cu-HCP / Cu-PHC
130,0	118,1	•	•
135,0	127,3	•	
140,0	136,9	•	
150,0	157,2	•	•
160,0	178,9	•	
170,0	201,9	•	
180,0	226,4	•	•
190,0	252,2	•	
200,0	279,5	•	•
210,0	308,1	•	•
220,0	338,1	•	•
250,0	436,7	•	•
300,0	628,8	•	•